Data Sheet Single Phase EMI Filter – MF320 IEC Inlet with Fuse & Switch Type



Description

These series range of IEC Inlet type filters with fuse and Switch are designed to suppress undesirable electrical disturbances in Power Lines. They limit the amplitude of interfering voltages on AC power lines and prevent them from propagating into or out of the filtered equipment.

Features

Integral IEC Connector High Conducted attenuation performance Single/Double Fuse Option Rated currents up to 10 A Double Pole/Single Throw Switch Medical versions available

Applications


Medical Application Electrical & Electronic Equipment's Testing & Measurement Equipments Household equipment Rack mounting equipment

Typical circuit Diagram



Approvals & Compliance





Technical Specifications

Maximum Continuous Operating Voltage	: 250VAC	
Operating Frequency	: 50/60Hz	
Current ratings	: 1A to 10A @40°C	
High Potential test voltage	: L to G 2250VDC for 1 Minute	
	L to L 1450VDC for 1 Minute	
Overload Capability	: 135% of Rated current for 15 minutes	
Design Corresponding to	: UL1283, CSA 22.2 No.8-13 and IEC 60939	
Flammability corresponding to	: UL 94 V-0	
Temperature range	: -25°C to +85⁰C	
Climatic Category	: 25/85/21	
Enclosure Material	: CRCA	


Images shown above are just for reference

Selection Table


Part Number	Ordering Code	Rated Current @40°C	Leakage Current @250VAC (mA)	Termination	Weight (Grams)
MF320 - 01	S320000001D	1A	0.34	Fastons 6.3 X 0.8mm	120
MF320 - 03	S320000003D	3A	0.34	Fastons 6.3 X 0.8mm	120
MF320 - 06	S320000006D	6A	0.34	Fastons 6.3 X 0.8mm	120
MF320 - 10	S320000010D	10A	0.34	Fastons 6.3 X 0.8mm	120

Note: Customized filters are provided on request.

Mechanical Drawing



Insertion Loss – (Common Mode)



EMI Solutions Private Ltd. #237-A5, Bommasandra Industrial Area, Bangalore-560099,

Marketing: +91 80 27836880, Email: marketing@emisindia.com